

© Feldbacher Thomas / Center of Competence/ tfeldbacher@otis.com



Technical drawing of a staircase detail showing the connection between a wall and a concrete slab. The drawing includes labels for 'Schachtseite' (shaft side), 'Teleskopelement oben' (telescopic element top), 'STL 2000', 'Portal 2218', 'EO 2250', 'Detail X', 'FFOK' (fire-protective floor construction), and 'Podestkante' (platform edge). Dimensions of 70 and 100 are indicated for the concrete slab thickness.

Technical drawing of a square concrete slab with dimensions and mounting hook specifications.

Dimensions:

- Overall width: 1600 mm (Schachtbreite 1600)
- Overall height: 1545 mm
- Inner width: 888 mm
- Inner height: 1000 mm (1000 mm = 100 mm + 900 mm)
- Top edge offset: 95 mm
- Bottom edge offset: 131 mm
- Left edge offset: 307 mm
- Right edge offset: 712 mm
- Bottom edge offset: 215 mm

Mounting Hook Specifications:

- Model: **LH** (Leifheit)
- Type: **Montagehaken bauseits**
- Product: **HALFEN HLX Lift-Box**
- Tragkraft [KN]:
 - LH1 = 20
 - LH2 = ---
 - LH3 = ---

Additional Information:

- HALFEN Ges.m.b.H.
- Leonard-Bernstein-Str. 10
- A-1220 Wien
- Tel. +43 (0) 259 6770

Podestkante

100

200

2x Durchbrüche
für Kabeldurchführungen
-50x300 vom FFOK+1.50
-50x300 vom FFOK+1.03

330

95

Haltestelle

Schachtbreite

700

500

Schaltsschrank nur in
der obersten Haltestelle!
2100mm hoch,
versperbar

Beleuchtungsstärke vor dem
Schaltsschrank min. 200 Lux

Technical drawing of a shaft cross-section. The drawing shows a central shaft with a diameter of 2218 mm. The shaft is supported by bearings (STL 2000) and has a total height of 2200 mm. The shaft is surrounded by a housing with a total height of 3450 mm. The shaft is labeled with 'Schachtentlüftung siehe bauseitige Leistungen' (Shaft ventilation see on-site services). The shaft is also labeled with 'Kabinenhöhe 2200' (Cabin height 2200), 'STL 2000', 'Portal 2218', 'EÖ 2250', 'oberste Haltestelle' (top stop), 'unterste Haltestelle' (bottom stop), 'Schachtkopf 3450' (Shaft head 3450), and 'SG 1000' (Safety height 1000). The shaft is also labeled with 'X' and 'FFC'.

C				F			
B				E			
A	16.12.2025	Feldbacher	Erstellung	D			
Index	Datum	Name	Änderungen:	Index	Datum	Name	Änderungen:
 Core MF0882NG							
Aufzugsart:		Personenaufzug			OTIS GesmbH Businesspark Maximum Modecenterstr. 17/ Objekt 1 A-1110 Wien Telefon +43(1) 610 05-0 www.otis.com		
Nennlast:	630	kg	Eigentümer:	Aufstellungsort: ---- ----			
Personenanzahl:	8		-				
Förderhöhe:	-	m	-				
Haltest./Ladest.:	-	/ -	-				
Fahrtgeschw.:	1,0	m/s					
Steuerung:	DCL					Zeichnungs-Nr.:	Index:
Maßstab: 1:25	Gez.: 16.12.2025	Feldbacher				Fabr.Nr.: 32N	A
	Gepr.:						