


© 2015 Pearson Education, Inc. or its affiliate(s). All rights reserved.



Technical drawing showing a detail of a staircase structure, labeled "Detail X". The drawing illustrates the side view of a wall and floor assembly.

Key components and labels:

- Schachseite**: Shaft side.
- Spalt oben und seitlich schließen (bauseits)**: Close top and side (building side).
- STL 2100**: Staircase landing (Stufenlauf).
- Portal 2318**: Portal frame.
- EO 2350**: External opening (Einbauelement).
- Detail X**: Section line indicating the detail location.
- FFOK**: Floor/Flooring (Fußboden).
- Podestkante**: Landing edge.
- Dimensions**: 70 and 100 (likely in mm).

Podestkante

1309

298

1500

Schachttiefe 1500

620

150

169

371

848

662

Schachtbreite 1510

Einstieg

Freigabe nur nach technischer Klärung!

Schachtentlüftung

LH1

LH1

LH2

LH3

LH

Montagehaken bauseits
HALFEN HLX Lift-Box

HLX Lift Box Link

Tragkraft [kN]:

HL1= 20
HL2= ---
HL3= ---

Kettenglied

HALFEN Ges.m.b.H.
Leonard-Bernstein-Str. 10
A-1220 Wien
Tel. +43 (0) 299 6770

Podestkante

100

200

2x Durchbrüche
für Kabeldurchführungen
-50x300 vom FFOK+1.13
-50x300 vom FFOK+1.60

330

20

Haltestelle

Schachtbreite

700

500

Schaltschrank nur in der obersten Haltestelle!
2100mm hoch, versperbar
Beleuchtungsstärke vor dem Schaltschrank min. 200 Lux

Technical drawing of a shaft (Schacht) cross-section. The drawing shows a central shaft with a diameter of 2100 mm, surrounded by a concrete structure. The total height of the shaft is 3450 mm. The shaft is divided into three sections: the top section (STL 2100) has a height of 2100 mm, the middle section (Portal 2318) has a height of 2318 mm, and the bottom section (EÖ 2350) has a height of 2350 mm. The shaft is supported by two holding points (Haltestelle) at the top and bottom. The bottom holding point is labeled 'unterste Haltestelle' and has a height of 1000 mm. The top holding point is labeled 'oberste Haltestelle' and has a height of 3450 mm. The shaft is also labeled 'Schachtkopf 3450' at the top. The drawing includes a section line 'X' and a dimension 'SG 1000' for the bottom section. The shaft is shown in a cross-section with a concrete structure. The drawing is labeled 'Schachtentlüftung siehe bauseitige Leistungen' at the top. The drawing is labeled 'Kabinenhöhe 2200' on the left side. The drawing is labeled 'Podestkante' at the bottom left. The drawing is labeled 'FFOK' at the bottom right.

Technical drawing of a window sill cross-section. The drawing shows a window frame with a sill. A vertical dimension line on the left indicates a 'Nische 70' (niche 70). A horizontal dimension line at the bottom indicates a 'Nische 100' (niche 100). A label 'Podestkante' (pedestal edge) points to the edge of the sill. The sill is shown with a cross-hatched pattern, and the window frame is shown with a solid line.

Stromversorgung: Anschlussspannung 3x400V, 50Hz;
Nennleistung: 3,71 kW, Nennstrom: 5,40 A, Anlaufstrom: 7,90 A (siehe auch Stromangaben Fa. OTIS).

C				F			
B				E			
A	17.03.2026	Feldbacher	Erstellung	D			
Index	Datum	Name	Änderungen:	Index	Datum	Name	Änderungen:
 MF0682NG							
Aufzugsart:				Personenaufzug			
Nennlast:		450 kg		Eigentümer:		OTIS GesmbH Businesspark Maximum Modecenterstr. 17/ Objekt 1 A-1110 Wien Telefon +43(1) 610 05-0 www.otis.com	
Personenanzahl:		6		----			
Förderhöhe:		- m		----			
Haltest./Ladest.:		- / -		----			
Fahrtgeschw.:		1,0 m/s					
Steuerung:		DCL		Aufstellungsort:			
Maßstab:1:25		Gez.: 17.03.2026 Feldbacher		----		Zeichnungs-Nr.:	
		Gepr.:		----		32N_-----	
						Fabr.Nr.: 32N	
						Index: A	